

Gas Detector



Personnel O2 Detector

- * Compact & rugged.
- * Over-molded boot.
- * One button operation.
- * Large backlit display.
- * Loud alarm.
- * Top & front mounted bright LED alarm light.
- * Translucent case option for enhanced alarm visibility
- * Optional built-in vibrating alarm.
- * Up to 9000 hour battery life
- * O2, CO, H2S, SO2, CO+, CO-H, Cl2, ClO2, NH3, NO2, PH3, HCN.
- * One-button automatic calibration.



Multi Gas Detector

- * One button operation.
- * Real time gas readings.
- * Easy-to-read front-mounted backlit graphic display.
- * Rated IPX5 for protection against water ingress.
- * Automatic low flow alarm.
- * Automatic leak test before every use.
- * Warning, Danger, STEL and TWA alarms.
- * Bright LED alarm light.
- * Loud audible alarm 92dBA at one foot.
- * Vibrating alarm optional.
- * Three sensors and up to four channels of direct detection.
O2, LEL, and a choice of CO, H2S or Duo-Tox two channel CO/H2S sensor.
- * Field replaceable sensors.
- * One button auto calibration.
- * Calibration due reminder.
- * Interchangeable alkaline or rechargeable (Li-Ion) versions.
- * Up to 22 hours run time depending on battery type (without pump).
- * Drop-in charger.



Personnel H2S detector

- * Compact & rugged.
- * One button operation.
- * Large display.
- * Loud alarm.
- * Top & front mounted bright LED.
- * Available with built-in vibrating alarm.
- * Exceeds IEC 6100-4-3 for level 3 RFI immunity specifications.
- * Displays service life remaining unless alarm condition is present.
- * During alarm condition, actual gas reading is shown.
- * O2, CO, H2S, or SO2.
- * One-button automatic calibration.

For further inquiries : technomarine@eim.ae, Fax: +971 6 5354 544, Tel: +971 6 5354 777

P.O. Box : 24293, Sharjah, United Arab Emirates, web : www.technomarineuae.com